



THE FLUTES IONIAN ARRAY

SPECIFICATIONS

Typical Lead Time 12-14 Weeks	Size 24 in	Length 4 IN	Color / Finish Satin Black	Accessory Finish Satin Brass
Color Temperature 3000K	Beam Angle 60° (Recommended)	Hexagonal Louver (Optional) Don't Include	Power Supply B. Standard Remote (2-Wire/TRIAC/FWD Phase, ELV, 0-10V)	Other Features Uplight & Downlight Powered Together
Total Wattage & Lumens 24 IN – 48W, 0-5200LM, Direct (4 Modules) & Indirect (4 Modules) 24 IN – 24W, 0-2600LM, Direct Only (4 Modules) 36 IN – 72W, 0-7800LM, Direct (6 Modules) & Indirect (6 Modules) 36 IN – 36W, 0-3900LM, Direct Only (6 Modules)	Light Quality 90 CRI	LED Lifespan 50,000 hrs, L80	Body Material Aluminum, solid brass, PMMA	Weight 4 IN x 24 IN – 6 lbs 8 IN x 24 IN – 9.5 lbs 4IN x 36 IN – 9 lbs 8 IN x 36 IN – 14 lbs
Mounting Mounted to ceiling using #8 wood screw	Certifications cUL, UL, CE, Title 24			

MORE INFORMATION & OPTIONS

Diameter Options 24 IN 36 IN Custom Diameters Available	Height Options 4 IN 8 IN Custom Lengths Available (5 IN-72 IN)	Color Temperature Options 2700K 3000K 3500K 4000K	Beam Angle Options 10° 36° 60° (Recommended)	Finish Options Satin Black with Satin Brass Connectors Satin Black with Black Oxide Connectors Satin Aluminum with Satin Brass Connectors Satin Aluminum with Black Oxide Connectors
Canopy Options 5" Junction Box Cover Plate included	Dimming Options 2-Wire/TRIAC/Forward Phase 0-10V 3-Wire/Ecosystem	Power Supply Options B – Standard Remote, 2-Wire/TRIAC/Forward-Pha se, 0-10V, ELV D – Lutron Remote, 2-Wire/TRIAC/Forward-Pha se E – Lutron Remote, 3-Wire/Ecosystem		

triode