



THE FLUTES LYDIAN ARRAY

SPECIFICATIONS

Typical Lead Time 12-14 Weeks	Size 48 in	Color / Finish Satin Black	Color Temperature 3000K	Beam Angle 60° (Recommended)
Power Supply B. Standard Remote (2-Wire/TRIAC/FWD Phase, ELV, 0-10V)	Hexagonal Louver (Optional) Don't Include	Other Features Uplight & Downlight Powered Together	Total Wattage & Lumens 48 IN – 42W, 0-4550LM, Direct (4 Modules) & Indirect (3 Modules) 48 IN – 24W, 0-2600LM, Direct Only (4 Modules) 62 IN – 48W, 0-5200LM, Direct (5 Modules) & Indirect (3 Modules) 62 IN – 30W, 0-3250LM, Direct Only (5 Modules)	Light Quality 90 CRI
LED Lifespan 50,000 hrs, L80	Body Material Aluminum, PMMA	Weight 48 IN – 10 lbs 62 IN – 13 lbs	Mounting Mounted to ceiling using #8 wood screw	Certifications cUL, UL, CE, Title 24

MORE INFORMATION & OPTIONS

Length Options 48 IN 62 IN Custom Extrusion Lengths Available (5 IN-72 IN)	Color Temperature Options 2700K 3000K 3500K 4000K	Beam Angle Options 10° 36° 60° (Recommended)	Finish Options Satin Black Satin Aluminum	Canopy Options Lydian Canopy for Local & Remote Installations 5" Junction Box Cover Plate included
Dimming Options 2-Wire/TRIAC/Forward Phase 0-10V 3-Wire/Ecosystem	Power Supply Options B – Standard Remote, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV D – Lutron Remote, 2-Wire/TRIAC/Forward-Phase E – Lutron Remote, 3-Wire/Ecosystem			

triode