



THIN CHANDELIER

SPECIFICATIONS

Typical Lead Time 12-14 Weeks	Color / Finish Satin Brass	Color Temperature 3000K	Power Supply A. Standard Local (2-Wire/TRIAC/FWD Phase)	Canopy 12.5" Canopy
Delivery Requirements Access to Loading Dock	Total Wattage & Lumens 48W, 0-5300LM	Light Quality CRI 95+, R9 90+ Frosted lens	LED Lifetime 50,000 hours	Body Material Solid Brass, PMMA
Weight 15 lbs	Canopy 12.5" Canopy in matching finish White canopy available upon request	Suspension & Mounting 115" aircraft cable with gripper and cable coupler provided 16' silver cord field adjustable	Certifications cUL, CE, UL	

MORE INFORMATION & OPTIONS

Designer Peter Bristol	Size Options 87 IN Diameter, Expanded	Color Temperature Options 2700K 3000K 3500K 4000K	Dimming Options 2-Wire/TRIAC/Forward-Phase 3-Wire/Ecosystem 0-10V ELV	Power Supply Options A - Standard Local, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV B - Standard Remote, 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV E - Lutron Remote, 3-Wire/Ecosystem
Finish Options Satin Brass Satin Nickel Black Oxide				

triode