



## THIN MULTIPLES TETRAD

### SPECIFICATIONS

**Segment Length**  
24 in [61 cm]

**Color Temperature**  
3000K

**Connected Sections**  
1 Section

**Power Supply**  
R. Standard Remote  
120-277V |  
2-Wire/TRIAC/Forward-Phase, 0-10V,  
ELV/Reverse-Phase

**Mounting**  
Direct-Mount to Ceiling

**Canopy**  
5" Cover Plate - Remote  
Power Only

**Color / Finish**  
Satin Brass

**Lens Finish**  
Frosted

## MORE INFORMATION & OPTIONS

---

### LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

### LED LIFESPAN

1 50,000 hrs, L80 32.00125

### BODY MATERIAL

2 Solid Brass, PMMA  
32.00125

### CERTIFICATIONS

3 cUL, UL, CE, Damp  
Location Rated, Title 24  
32.00125

### DESIGNER

4 Peter Bristol 32.00125

### WATTAGE & LUMENS (PER SECTION)

5 24 IN – 27.2W, 0-2400LM  
36 IN – 38.4W, 0-3680LM  
47.50125

### WEIGHT

6 36 IN – 4 lbs  
24 IN – 2.6 lbs 44.50125

### MOUNTING

7 10ft 1/16" aircraft cable,  
field adjustable  
16ft Clear-jacketed 22AWG  
co-axial silver cord, field  
adjustable  
Direct-mounting and  
center-mounting with  
Linear Cable Collar options  
available (for up to 2  
connected sections)  
44.50125