



THIN MULTIPLES VERTICAL SUSPENSION TETRAD

SPECIFICATIONS

Segment Length
24 in [61 cm]

Color / Finish
Satin Brass

Lens Finish
Frosted

Color Temperature
2700K

Power Supply
R. Standard Remote
120-277V |
2-Wire/TRIAC/Forward-Phase,
0-10V,
ELV/Reverse-Phase

Canopy
5" Cover Plate - Remote
Power Only

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 24 IN – 27.2W, 0–2400LM
36 IN – 38.4W, 0–3680LM
44.50125

WEIGHT

6 36 IN – 4 lbs
24 IN – 2.6 lbs 44.50125

MOUNTING

7 10ft 1/16" aircraft cable,
field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable 44.50125