



THIN PRIMARIES HEXAGON

SPECIFICATIONS

Mounting

Center-Mount to Canopy

Power Supply

R. Standard Remote

120-277V |

2-Wire/TRIAC/Forward-Phase

se, 0-10V,

ELV/Reverse-Phase

Segment Length

24 in [61 cm]

Canopy

5" Cover Plate - Remote

Power Only

Color / Finish

Satin Brass

Color Temperature

3000K

Lens Finish

Frosted

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 24 IN – 40.8W, 0-3600LM
36 IN – 57.6W, 0-5500LM
44.50125

WEIGHT

6 24 IN – 3.4 lbs
36 IN – 4.2 lbs 44.50125

MOUNTING

7 (x6) 1/16" aircraft cables,
field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
Direct-mounting and
center-mounting options
available
Cable Collar in matching
finish optional for
center-mounting 44.50125