



## THIN PRIMARIES RHOMBUS

### SPECIFICATIONS

**Mounting**

Center-Mount to Canopy

**Power Supply**

R. Standard Remote  
120-277V |  
2-Wire/TRIAC/Forward-Phase, 0-10V,  
ELV/Reverse-Phase

**Segment Length**

24 in [61 cm]

**Canopy**

5" Cover Plate - Remote  
Power Only

**Color / Finish**

Satin Brass

**Color Temperature**

3000K

**Lens Finish**

Frosted

## MORE INFORMATION & OPTIONS

---

### LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

### LED LIFESPAN

1 50,000 hrs, L80 32.00125

### BODY MATERIAL

2 Solid Brass, PMMA  
32.00125

### CERTIFICATIONS

3 cUL, UL, CE, Damp  
Location Rated, Title 24  
32.00125

### DESIGNER

4 Peter Bristol 32.00125

### WATTAGE & LUMENS

5 24 IN – 27.2W, 0-2400LM  
36 IN – 38.4W, 0-3700LM  
44.50125

### WEIGHT

6 24 IN – 2.6 lbs  
36 IN – 3.3 lbs 44.50125

### MOUNTING

7 (x4) 1/16" aircraft cables,  
field adjustable  
16ft Clear-jacketed 22AWG  
co-axial silver cord, field  
adjustable  
Direct-mounting and  
center-mounting options  
available  
Cable Collar in matching  
finish optional for  
center-mounting 44.50125