



THIN PRIMARIES SQUARE

SPECIFICATIONS

Mounting

Center-Mount to Canopy

Power Supply

R. Standard Remote

120-277V |

2-Wire/TRIAC/Forward-Phase

se, 0-10V.

ELV/Reverse-Phase

Segment Length

24 in [61 cm]

Canopy

5" Cover Plate - Remote

Power Only

Color / Finish

Satin Brass

Color Temperature

3000K

Lens Finish

Frosted

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 24 IN – 27.2W, 0-2400LM
36 IN – 38.4W, 0-3700LM
44.50125

WEIGHT

6 24 IN – 2.6 lbs
36 IN – 3.3 lbs 44.50125

MOUNTING

7 (x4) 1/16" aircraft cables,
field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
Direct-mounting and
center-mounting options
available
Cable Collar in matching
finish optional for
center-mounting 44.50125