



THIN PRIMARIES WALL-MOUNTED SQUARE

SPECIFICATIONS

Segment Length
24 in [61 cm]

Standoff Height
3.5 in [90 mm]

Color / Finish
Satin Brass

Color Temperature
3000K

Lens Finish
Frosted

Power Supply

R. Standard Remote
120-277V |
2-Wire/TRIAC/Forward-Phase
se, 0-10V,
ELV/Reverse-Phase

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 24 IN – 27.2W, 0-2400LM
36 IN – 38.4W, 0-3700LM
44.50125

WEIGHT

6 24 IN – 3.44 lbs
36 IN – 4.12 lbs 44.50125

MOUNTING

7 Wall brackets mount
directly to surface
2 X 18AWG in-wall rated
cable recommended for
remote installation
(provided by electrician)
44.50125