



THIN SOLIDS TETRAHEDRON

SPECIFICATIONS

Mounting

1 Mounting Point

Segment Length

18 in [45.7 cm]

Color / Finish

Satin Brass

Color Temperature

3000K

Lens Finish

Frosted

Power Supply

R. Standard Remote
120-277V |
2-Wire/TRIAC/Forward-Phase, 0-10V,
ELV/Reverse-Phase

Canopy

5" Cover Plate - Remote
Power Only

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 12 IN – 20.4W, 0-1800LM
18 IN – 30.6W, 0-2700LM
24 IN – 40.8W, 0-3600LM
44.50125

WEIGHT

6 12 IN – 4 lbs
18 IN – 3.5 lbs
24 IN – 3 lbs 44.50125

MOUNTING

7 (x1 or x3) 1/16" aircraft
cables, field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
1 or 3 mounting point
options 44.50125