



THIN SOLIDS CUBE

SPECIFICATIONS

Mounting

1 Mounting Point

Power Supply

R. Standard Remote

120-277V |

2-Wire/TRIAC/Forward-Phase

se, 0-10V,

ELV/Reverse-Phase

Segment Length

18 in [45.7 cm]

Canopy

5" Cover Plate - Remote

Power Only

Color / Finish

Satin Brass

Color Temperature

3000K

Lens Finish

Frosted

MORE INFORMATION & OPTIONS

LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

LED LIFESPAN

1 50,000 hrs, L80 32.00125

BODY MATERIAL

2 Solid Brass, PMMA
32.00125

CERTIFICATIONS

3 cUL, UL, CE, Damp
Location Rated, Title 24
32.00125

DESIGNER

4 Peter Bristol 32.00125

WATTAGE & LUMENS

5 12 IN – 40.8W, 0–3600LM
18 IN – 61.2W, 0–5400LM
24 IN – 81.6W, 0–7200LM
44.50125

WEIGHT

6 12 IN – 7 lbs
18 IN – 8 lbs
24 IN – 9 lbs 44.50125

MOUNTING

7 (x1, x2, or x4) 1/16" aircraft
cables, field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
1, 2, or 4 mounting point
options 44.50125