



THIN PRIMARIES HEXAGON

SPECIFICATIONS

Typical Lead Time
6-8 Weeks

Mounting
Center-Mount to Canopy

Segment Length
24 in [61 cm]

Color / Finish
Satin Brass

Color Temperature
3000K

Lens Finish
Frosted

Power Supply
B. Standard Remote
(2-Wire/TRIAC/FWD Phase,
ELV, 0-10V)

Canopy
5" Cover Plate - Remote
Power Only

Total Wattage & Lumens/Fixture
24 IN - 40.8W, 0-3600LM
36 IN - 57.6W, 0-5500LM

Light Quality
CRI 95+, R9 90+

LED Lifespan
50,000 hrs, L80

Body Material
Solid Brass, PMMA

Weight
24 IN - 3.4 lbs
36 IN - 4.2 lbs

Power
24VDC output Class 2
constant voltage power
supply
120VAC input voltage

Mounting
(x6) 1/16" aircraft cables,
field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
Direct-mounting and
center-mounting options
available
Cable Collar in matching
finish optional for
center-mounting

Certifications
cUL, UL, CE, Damp Location
Rated, Title 24

MORE INFORMATION & OPTIONS

Designer
Peter Bristol

Length Options
24 IN (53 IN x 44 IN Overall)
36 IN (77 IN x 66 IN Overall)

Color Temperature Options
2700K
3000K
3500K
4000K

Finish Options
Satin Brass
Satin Nickel
Black Oxide

Dimming Options
2-Wire/TRIAC/Forward
Phase
0-10V
3-Wire/Ecosystem

Power Supply Options
A - Standard Local,
2-Wire/TRIAC/Forward-Phase,
0-10V, ELV
B - Standard Remote,
2-Wire/TRIAC/Forward-Phase,
0-10V, ELV
D - Lutron Remote,
2-Wire/TRIAC/Forward-Phase
E - Lutron Remote,
3-Wire/Ecosystem

Canopy Options
7" Local Canopy for Local
Power <54W
12.5" Local Canopy for
Local Power >55W
5" Cover Plate for Remote
Power
Remote Power Cord
Gripper

Optional Accessories
Center-Mounting Cable
Collar Available for
Suspended Fixtures

triode